



THE GREEN YARDSTICK



ENVIRONMENTAL PRODUCT DECLARATION

In accordance with EN 15804 and ISO 14025

Ecophon Hygiene™

Realization date : 2015-10-26
Version : 1.0






The environmental impacts of this product have been assessed over its whole life cycle. Its Environmental Product Declaration has been verified by an independent third party.

Ecophon®
SAINT-GOBAIN

A SOUND EFFECT ON PEOPLE

Summary Environmental product declaration

| Content summary | |
|---|--|
| Verified by (external third party verifier) | Martin Erlandsson, DNV GL |
| Programme used | The International EPD System. For more information see www.environdec.com |
| Registration No | S-P-00793 |
| Owners declaration by | Saint-Gobain Ecophon AB Box 500 265 03 Hyllinge Sweden |
| Declaration as construction products | The products to be verified herein are acoustic glass wool panels made for sound absorbing ceilings. The present environmental product declaration complies with standard ISO 14025 and describes the environmental impact. Its purpose is to promote compatible and sustainable environmental development of related construction methods. Reference PCR document: EN 15804 as the core PCR + International EPD System Product Category Rule, PCR for constructions products and construction services, PCR 2012:01, version 2.0, 2015-03-03, with the appendix _SUB PCR "Acoustic ceilings". <i>EPD of construction products may not be comparable if they do not comply with EN 15804.</i> |
| Validity | 2020-10-26 |
| Content of the declaration | This is a general environmental declaration of the product family Hygiene. The values presented in this EPD are based on a mean value calculated from sales statistics for 2014 of the following products: Foodtec A, Foodtec Wall Foodtec Baffle Protec A, Performance A Meditec A, Meditec E Labotec Air A, Labotec Ds The LCA values given in this EPD are not valid for any of the above products but give an average value for the Hygiene family product. Supplement EPD with detailed product information can be found at www.ecophon.com |
| UN CPC (Central Product Classification) CODE | 37990 37129 |
| Issued date | 2015-10-26 |
| Signature | |
|  Daniel Olausson Product Engineer Saint-Gobain Ecophon AB  Anna Palminger Environmental specialist Saint-Gobain Ecophon AB | Third party verifier:  Martin Erlandsson, DNV GL (Independent third party verifier) |

Product description

Product description and description of use:

This Environmental Product Declaration (EPD) describes the environmental impact of 1m² of acoustic ceiling with the intended use to increase sound absorption in a room to create a better indoor environment.

The production site of Saint-Gobain Ecophon (Sweden) produces acoustic ceilings and wall absorbers based on glass wool with a plant based binder in different densities and thicknesses. The glass wool is covered with a painted or woven surface layer and cut into panels of different sizes and edge designs. The edges are painted and the panels are packed in cardboard boxes.

The structure of glass wool gives the material excellent sound energy absorption properties. Sound absorption is the main function of acoustic glass wool panels. The panels are also light, stable, and easy to handle and cut.

Acoustic glass wool panels are commonly used in schools, offices, health care facilities and production premises where there is a need for noise reduction to improve the working environment. The decrease in reverberation time, sound pressure level and other acoustic parameters are related to the amount of panels used in the room as well as the placement of the panels.

The acoustic panels need no maintenance and do not age. They can last as long as the building itself. For aesthetic reasons, normal room surface cleaning is advised.

Description of the main product components and materials for 1 m² of product:

| PARAMETER | VALUE (WEIGHT IN %) | POST CONSUMER RECYCLED CONTENT |
|-------------------|---------------------|--------------------------------|
| Product thickness | 21,4mm | - |
| Glass wool | 63% | 70% |
| Water based paint | 29% | - |
| Glass tissue | 5% | - |
| Water based glue | 3% | - |

(Total weight of product is calculated to 2056g)

All raw materials contributing more than 5% to any environmental impact are listed in the table above. The panels are free from substances of very high concern (SVHC). The product contains no substances from the REACH Candidate list (of 15.06.2015).

If there for some reason is a variation greater than 10% on the environmental effects in any of the categories of impact this EPD has to be updated and re-verified.

Other environmental indicators

Regarding the indoor environment, the Hygiene products are certified for or fulfil regulations according to the following table:

| CERTIFICATE AND REGULATIONS |
|---|
| Finnish M1 |
| French VOC A+ |
| Danish Indoor climate |
| California emission regulation (CDPH-IAQ) |



LCA calculation information

| | |
|--|---|
| DECLARED UNIT | 1m ² of acoustic ceiling panel. |
| FUNCTIONAL UNIT | 1m ² acoustic ceiling with sound absorption class A installed at an ODS of 200mm according to ISO 354. |
| SYSTEM BOUNDARIES | Cradle to grave: Mandatory stages = A1-3, A4-5, B1-7, C1-4 and optional stage = D This EPD covers the environmental impact of acoustic panels without grid or suspension system. |
| REFERENCE SERVICE LIFE (RSL) | 50 years |
| CUT-OFF RULES | The use of cut-off criterion on mass inputs and primary energy at the unit process level (1%) and at the information module level (5%). Flows related to human activities such as employee transport are excluded. The construction of plants, production of machines and transportation systems are excluded since the related flows are supposed to be negligible compared to the production of the building product when compared at these systems lifetime level. |
| ALLOCATIONS | Allocation criteria are based on mass. |
| GEOGRAPHICAL COVERAGE AND TIME PERIOD | Europe 2013 |

According to EN 15804, EPD of construction products might not be comparable if they do not comply with this standard. According to ISO 21930, EPD's might not be comparable if they are from different EPD administrating schemes.

Life Cycle stages

Flow diagram of the Life Cycle



Product stage, A1-A3

Description of the stage:

The product stage of the glass wool products is divided into 3 modules: A1 "Raw material and supply", A2 "Transport to the manufacturer" and A3 "Manufacturer"

The aggregation of the modules A1, A2 and A3 is a possibility considered by the EN 15 804 standard. This rule is applied in this EPD.

A1 Raw material supply

This module takes into account the extraction and processing of all raw materials and energy which occur upstream to the studied manufacturing process.

Specifically, the glass wool raw material supply covers production of the plant based binder components and sourcing (quarry) of raw materials for fiber production, e.g. sand and borax. Besides these raw materials, recycled materials (glass cullet) are also used as input. Other major raw materials are paint, glass tissue and glue which also are included in the calculation.

A2 Transport to the manufacturer

The raw materials are transported to the manufacturing site. In our case, the modelling include: road, boat or train transportations (average values) of each raw material.

A3 Manufacturing

The manufacturing includes two steps; glass wool production and glass wool panel production. The glass wool panels are produced in a continuous online process starting with applying glass tissue on the glass wool baseboard. The panels are cut into correct size and the edges of the panels are painted. After drying the panels are packed in cardboard boxes.

Manufacturing covers all processes linked to production, which comprises various related operations besides on-site activities such as grinding, painting and drying, packaging and internal transportation. The manufacturing process also yields data on the combustion of refinery products, such as natural gas, diesel and gasoline, related to the production process.

The environmental profile of these energy carriers is modelled for local conditions.

Packaging-related flows in the production process and all up-stream packaging are included in the manufacturing module, i.e. wooden pallets, cardboard and PE-film.

Apart from production of packaging material, the supply and transport of packaging material are also considered in the LCA model. They are reported and allocated to the module where the packaging is applied. Data on packaging waste created during this step is then generated.

It is assumed that packaging waste generated in the course of production and up-stream processes is 100% collected and either recycled or incinerated with energy recovery, related to material and quality, in ratios according to the local material handling companies.

Construction process stage, A4-A5

Description of the stage:

The construction process is divided into 2 modules: A4 "Transport to the building site" and A5 "Installation in the building."

Description of scenarios and additional technical information:

A4 Transport to the building site

This module includes transport from the production gate to the building site.

Transport is calculated on the basis of a scenario with the parameters described in the following table.

| PARAMETER | VALUE |
|--|---|
| Fuel type, consumption of fuel and vehicle or vehicle type used for transport | Average truck trailer with a 24t payload, diesel consumption 38 litres for 100 km |
| Distance | 991 km (based on yearly statistics for 2014) |
| Capacity utilisation (including empty returns) | 100% of the capacity in volume 30% of empty returns |
| Bulk density of transported products (if available) | 61 kg/m ³ |
| Volume capacity utilisation factor (if available) | 1 |

A5:1 Installation in the building

This module includes waste of products during the implementation, the additional production processes to compensate the loss and the waste processing which occur in this stage.

Scenarios used for quantity of product wastage and waste processing are:

| PARAMETER | VALUE |
|--|---|
| Waste of materials on the building site before waste processing, generated by the product's installation (specified by type) | 5% |
| Output materials (specified by type) as results of waste processing at the building site e.g. of collection for recycling, for energy recovering, disposal | Packaging waste is 100 % collected and modelled as recovered matter Glass wool losses are landfilled |

A5:2 Energy usage

As a general figure the time to install 1m² ceiling is considered to be 20 minutes. During this time the installer is considered to use handheld appliances for about 5% of this time which in this case results in 1 minute. An average handheld appliance power usage is approximately 0,025kw/h which gives a value of $0,025 \cdot 0,016 = 4,16W/m^2$ ceiling. In this context it is a negligible contribution and will not be part of the LCA calculation.

Use stage (excluding potential savings), B1-B7

Description of the stage:

The use stage is divided into 7 modules, B1 "Use", B2 "Maintenance", B3 "Repair", B4 "Replacement", B5 "Refurbishment", B6 "Operational energy use", B7 "Operational water use"

Description of scenarios and additional technical information:

Once installation is complete, no actions or technical operations are required during the use stages until the end of life stage. Therefore glass wool ceiling panels have no impact (excluding potential energy savings) on this stage.

End-of-life stage C1-C4

Description of the stage:

The end-of life stage is divided into 4 modules; C1 "De-construction, demolition", C2 "Transport to waste processing", C3 "Waste processing for reuse, recovery and/or recycling", C4 "Disposal".

Description of scenarios and additional technical information:

C1, De-construction, demolition

The de-construction and/or dismantling of glass wool ceiling panels take part during the renovation of the building or the demolition of the entire building. In our case, the environmental impact is assumed to be very small and can be neglected.

C2, Transport to waste processing

The model for transportation (see A4, Transportation to the building site) is applied.

C3, Waste processing for reuse, recovery and/or recycling;

The product is considered to be landfilled without reuse, recovery or recycling.

C4, Disposal;

The product is assumed to be 100% landfilled.

| PARAMETER | VALUE/DESCRIPTION |
|---|---|
| Collection process specified by type | 2056g of acoustic ceiling (collected with mixed construction waste) |
| Recovery system specified by type | No reuse, recycling or energy recovery |
| Disposal specified by type | 1298g of glass wool is landfilled |
| Assumptions for scenario development (e.g. transportation) | Average truck trailer with a 24t payload, diesel consumption 38 litres for 100 km |
| | 25 km (distance to landfill) |

Reuse/recovery/recycling potential, D

Description of scenarios and additional technical information:

Packaging waste from module A5 is reported in this module as recovered matter.

LCA results

LCA model, aggregation of data and environmental impact are calculated from the TEAM™ software 5.2.





Raw materials and energy consumption, as well as transport distances have been taken directly from the manufacturing plant of Saint-Gobain Ecophon in 2013.

Summary of the LCA results are detailed on the following tables.

All results in the EPD are written in logarithmic base of ten. Reading example: $5.2E -03 = 5.2 \cdot 10^{-3} = 0,0052$.

MND (module not declared), is equal to MNA (module not assessed).

ENVIRONMENTAL IMPACTS

| Parameters | Product stage | Construction process stage | | Use stage | | | | | | | End-of-life stage | | | | D Reuse, recovery, recycling |
|--|---------------|----------------------------|-----------------|-----------|----------------|-----------|----------------|------------------|---------------------------|--------------------------|--------------------------------|--------------|---------------------|-------------|------------------------------|
| | A1/A2/A3 | A4 Transport | A5 Installation | B1 Use | B2 Maintenance | B3 Repair | B4 Replacement | B5 Refurbishment | B6 Operational energy use | B7 Operational water use | C1 Deconstruction / demolition | C2 Transport | C3 Waste processing | C4 Disposal | |
|  Global Warming Potential (GWP) - <i>kg CO₂ equiv/FU</i> | 3,4E+00 | 4,4E-01 | 1,9E-01 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,1E-02 | 0 | 0 | MND |
| The global warming potential of a gas refers to the total contribution to global warming resulting from the emission of one unit of that gas relative to one unit of the reference gas, carbon dioxide, which is assigned a value of 1. | | | | | | | | | | | | | | | |
|  Ozone Depletion (ODP) <i>kg CFC 11 equiv/FU</i> | 4,5E-07 | 3,1E-07 | 3,8E-08 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1,5E-08 | 0 | 0 | MND |
| Destruction of the stratospheric ozone layer which shields the earth from ultraviolet radiation harmful to life. This destruction of ozone is caused by the breakdown of certain chlorine and/or bromine containing compounds (chlorofluorocarbons or halogens), which break down when they reach the stratosphere and then catalytically destroy ozone molecules. | | | | | | | | | | | | | | | |
|  Acidification potential (AP) <i>kg SO₂ equiv/FU</i> | 1,9E-02 | 2,6E-03 | 1,1E-03 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1,3E-04 | 0 | 0 | MND |
| Acid depositions have negative impacts on natural ecosystems and the man-made environment incl. buildings. The main sources for emissions of acidifying substances are agriculture and fossil fuel combustion used for electricity production, heating and transport. | | | | | | | | | | | | | | | |
|  Eutrophication potential (EP) <i>kg (PO₄)³⁻ equiv/FU</i> | 2,4E-03 | 6,5E-04 | 1,5E-04 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3,1E-05 | 0 | 8,1E-06 | MND |
| Excessive enrichment of waters and continental surfaces with nutrients, and the associated adverse biological effects. | | | | | | | | | | | | | | | |
|  Photochemical ozone creation (POPC) <i>kg Ethene equiv/FU</i> | 1,2E-03 | 5,9E-05 | 6,4E-05 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,8E-06 | 0 | 0 | MND |
| Chemical reactions brought about by the light energy of the sun. The reaction of nitrogen oxides with hydrocarbons in the presence of sunlight to form ozone is an example of a photochemical reaction. | | | | | | | | | | | | | | | |
|  Abiotic depletion potential for non-fossil resources (ADP-elements) - <i>kg Sb equiv/FU</i> | 5,1E-07 | 6,4E-11 | 2,6E-08 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3,1E-12 | 0 | 0 | MND |
|  Abiotic depletion potential for fossil resources (ADP-fossil fuels) - <i>MJ/FU</i> | 6,3E+01 | 5,4E+00 | 3,4E+00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,6E-01 | 0 | 0 | MND |
| Consumption of non-renewable resources, thereby lowering their availability for future generations. | | | | | | | | | | | | | | | |





RESOURCE USE

| RESOURCE USE | | | | | | | | | | | | | | | |
|---|---------------|----------------------------|-----------------|-----------|----------------|-----------|----------------|------------------|---------------------------|--------------------------|--------------------------------|--------------|---------------------|-------------|------------------------------|
| Parameters | Product stage | Construction process stage | | Use stage | | | | | | | End-of-life stage | | | | D Reuse, recovery, recycling |
| | A1 / A2 / A3 | A4 Transport | A5 Installation | B1 Use | B2 Maintenance | B3 Repair | B4 Replacement | B5 Refurbishment | B6 Operational energy use | B7 Operational water use | C1 Deconstruction / demolition | C2 Transport | C3 Waste processing | C4 Disposal | |
| Use of renewable primary energy excluding renewable primary energy resources used as raw materials - MJ/FU | 2,4E+01 | 3,0E-03 | 1,4E+00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1,5E-04 | 0 | 0 | MND |
| Use of renewable primary energy used as raw materials MJ/FU | 3,9E+00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | MND |
| Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials) MJ/FU | 2,8E+01 | 3,0E-03 | 1,4E+00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1,5E-04 | 0 | 0 | MND |
| Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials - MJ/FU | 6,1E+01 | 5,5E+00 | 4,2E+00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,6E-01 | 0 | 0 | MND |
| Use of non-renewable primary energy used as raw materials MJ/FU | 1,7E+01 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | MND |
| Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials) - MJ/FU | 7,8E+01 | 5,5E+00 | 4,2E+00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,6E-01 | 0 | 0 | MND |
| Use of secondary material kg/FU | 1,3E+00 | 0 | 6,3E-02 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | MND |
| Use of renewable secondary fuels- MJ/FU | - | - | - | - | - | - | - | - | - | - | - | - | - | - | MND |
| Use of non-renewable secondary fuels - MJ/FU | - | - | - | - | - | - | - | - | - | - | - | - | - | - | MND |
| Use of net fresh water - m³/FU | 5,2E-02 | 5,2E-04 | 2,6E-03 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,5E-05 | 0 | 0 | MND |

WASTE CATEGORIES

| Parameters | Product stage | Construction process stage | | Use stage | | | | | | | End-of-life stage | | | | D Reuse, recovery, recycling |
|--|---------------|----------------------------|-----------------|-----------|----------------|-----------|----------------|------------------|---------------------------|--------------------------|--------------------------------|--------------|---------------------|-------------|------------------------------|
| | A1 / A2 / A3 | A4 Transport | A5 Installation | B1 Use | B2 Maintenance | B3 Repair | B4 Replacement | B5 Refurbishment | B6 Operational energy use | B7 Operational water use | C1 Deconstruction / demolition | C2 Transport | C3 Waste processing | C4 Disposal | |
| Hazardous waste disposed <i>kg/FU</i> | 2,7E-02 | 1,6E-04 | 1,4E-03 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7,8E-06 | 0 | 0 | MND |
| Non-hazardous waste disposed <i>kg/FU</i> | 4,5E-01 | 4,3E-04 | 1,3E-01 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2,1E-05 | 0 | 2,1E+00 | MND |
| Radioactive waste disposed <i>kg/FU</i> | 3,8E-04 | 8,7E-05 | 2,3E-05 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4,2E-06 | 0 | 0 | MND |

OUTPUT FLOWS

| OUTPUT FLOWS | | | | | | | | | | | | | | | |
|--|---------------|----------------------------|-----------------|-----------|----------------|-----------|----------------|------------------|---------------------------|--------------------------|--------------------------------|--------------|---------------------|-------------|------------------------------|
| Parameters | Product stage | Construction process stage | | Use stage | | | | | | | End-of-life stage | | | | D Reuse, recovery, recycling |
| | A1 / A2 / A3 | A4 Transport | A5 Installation | B1 Use | B2 Maintenance | B3 Repair | B4 Replacement | B5 Refurbishment | B6 Operational energy use | B7 Operational water use | C1 Deconstruction / demolition | C2 Transport | C3 Waste processing | C4 Disposal | |
|  Components for re-use <i>kg/FU</i> | - | - | - | - | - | - | - | - | - | - | - | - | - | - | MND |
|  Materials for recycling <i>kg/FU</i> | 6,6E-01 | 2,2E-06 | 2,7E-01 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1,0E-07 | 0 | 0 | MND |
|  Materials for energy recovery <i>kg/FU</i> | - | - | - | - | - | - | - | - | - | - | - | - | - | - | MND |
|  Exported energy, detailed by energy carrier <i>MJ/FU</i> | 3,0E-02 | 0 | 1,5E-03 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | MND |

LCA interpretation



[1] This indicator corresponds to the abiotic depletion potential of fossil resources.

[2] This indicator corresponds to the total use of primary energy.

[3] This indicator corresponds to the use of net fresh water.

[4] This indicator corresponds to the sum of hazardous, non-hazardous and radioactive waste disposed.