

FAST

FAST FASTENING



BETONGSKR R-LX HF 5,0X50 ZF BRK=100

Betongskrue R-LX FAST

For direkte innfestning i betong. Skruen har Hi-Lo gjenger som gir en høy uttreksverdi. NB! Ved montering, bor alltid 10mm dypere enn skruelengden krever. Overflatebehandling: Zinkflakes, korrosjonsklasse C3. Boks.

Kataloginfo

Artikelnr	Dimension d x L mm	Borrdiameter mm	Nyckelvidd mm	Innehåll	Antal/fp
288301	5,0x50	5	8	100	8
288303	5,0x75	5	8	100	8
288305	6,0x50	6	10	50	8
288307	6,0x75	6	10	50	8
288309	6,0x100	6	10	50	6
288315	8,0x60	8	13	25	8
288317	8,0x75	8	13	25	8
288319	8,0x90	8	13	25	6
288321	8,0x100	8	13	25	6
288323	8,0x130	8	13	25	6
288329	10,0x65	10	15	20	8
288331	10,0x85	10	15	20	6
288333	10,0x100	10	15	20	6
288335	10,0x120	10	15	20	6

Teknisk data

Skruv dimension mm	Borrdiameter mm	Min monteringsdjup mm	Praktisk lastförmåga (kN)
Ø 6,0	6	40	2,08
Ø 8,0	8	55	5,00
Ø 10,0	10	70	9,00

no: <http://no.fast-fastening.com/fast/lboxServlet?p=IXK090&AID=288301>

