

PRIMO SAFE.T

TEKNISK DATA

SERTIFISERING & KLASSIFISERING	STANDARD	PRIMO SAFE.T
Type gulvbelegg	EN 13845	Sklihemmende homogent vinyl gulvbelegg
Klassifisering	EN ISO 10874	Offentlig: 34 Industri: 43
TEKNISKE SPESIFIKASJONER		
Total tykkelse	EN ISO 24346	2.0 mm
Total vekt	EN ISO 23997	3000 g/m ²
Overflatebehandling		Safe.T clean XP™
Leveres som	EN ISO 24341 Sheet (rolls)	Ca. 23 lm x 200 cm Art. nr. 21013_ _ _ 3 sifret fargenummer
YTELSER FOR Å TILFREDSSTILE CE MERKING (EN 14041)		
Ytelseserklæring	EN 14041	0019-0048-DoP-2013-07
Brannklassifisering	EN 13501-1	Klasse B _{fl} -s1
	EN ISO 9239-1	≥ 8 kW/m ²
	EN ISO 11925-2	Godkjent
Elektrostatisk oppladning	EN 1815	< 2 kV
Varmeledningsevne	EN 12667/DIN 52612	Ca. 0.01 m ² K/W
Sklihemmende egenskaper	EN 13893 /BS 7976-2	≥ 0.3 / Liten risiko
TEKNISKE EGENSKAPER		
Inntrykksmerker	EN ISO 24343-1	Krav: ≤ 0.10 mm Best målte verdi*: 0.03 mm
Sklihemmende egenskaper	DIN 51130	R10
Bakterie resistens	EN ISO 846: Part C	Fremmer ikke vekst
Kjemikaliebestandighet	ISO 26987	God bestandighet
Trinsehjul	ISO 4918	Egnet
Fleksibilitet	ISO 24344	Godkjent
Dimensjonsstabilitet	EN ISO 23999	≤ 0.40 %
Lysekthet	EN ISO 105-B02	≥ 6
Barfot test	DIN 51097	Klasse B (≥ 18°)
Styrke skjøt	EN 684	Individuell verdi: ≥ 400 N/50 mm
Gulvvarme		Egnet - maks. 27°C
INNEMILJØ		
Totale VOC emisjoner	ISO 16000-9 / Påvirkning av innemiljø ≤ 10 µg/m ³ (etter 28 dogn) / Platinum	
FARGER		

15

The above information is subject to modification for the benefit of further improvement. (04/18).
According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

*For information - not binding.

CUSTOMS TARIFF : 4820 5000 00

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.
Colours of the products shown in the photos or samples are indicative only. There may be differences in colours, gloss and embossing structure between the products sold and photos or samples.



PRIMO SAFE.T		
Artikkel	Fargenavn	WR (Multi)
21013790	lt pure grey	1290369
21013791	md pure grey	1290284
21013792	md grey	1290285
21013793	lt warm grey	1290286
21013794	md cool grey	1290287
21013795	dk cool grey	1290288
21013796	lt cool beige	1290289
21013797	md cool beige	1290290
21013798	dk cool beige	1290291
21013800	md warm-beige	1290293
21013801	dk warm-beige	1290368
21013802	lt green	1290295
21013803	md green	1290296
21013805	lt blue	1290370
21013806	md blue	1290299